



DESCRIPTION AND FIELD OF APPLICATION

Product description

Rosneft MOTO 4T 20W-50 is a multigrade mineral oil for small four-stroke gasoline engines of motorcycles, scooters and garden equipment. It is produced from high quality mineral base oil using a modern additive package.

Scope of application

Rosneft MOTO 4T 20W-50 is designed for use in small four-stroke gasoline engines and gearboxes of motorcycles, scooters and garden equipment requiring API SF and/or JASO MA2 oil.

APPROVALS AND SPECIFICATIONS

International specifications:

API SF, JASO MA2.

BENEFITS

- Reliable anti-wear protection of the engine and gearbox of motor vehicles from wear and corrosion;
- High thermal and oxidative stability to reduce the amount of deposits on engine parts;
- The highly effective detergent and dispersant additives in the oil prevent the formation of varnishes and deposits, which prolongs the engine life;
- Provides a crisp and smooth clutch response in various modes;
- Versatile use suitable for both motor vehicles and garden equipment.

PACKAGING

1 L, 4 L

Typical physical and chemical parameters

Parameter	Test method	Rosneft MOTO 4T 20W-50
Kinematic viscosity at 100 °C, mm ² /s	GOST 33	19.20
Viscosity index	GOST 25371	119
Base number, mg KOH/g	GOST 11362	7.15
Sulfate ash content, wt %	GOST 12417	0.98
Open cup flash point, °C	GOST 4333	224
Pour point, °C	GOST 20287	-20
Density at 15°C, kg/m ³	ASTM D1298	889.4