



## PRODUCT DESCRIPTION AND APPLICATION

### Product Description

**Rosneft MOTO 2T** is a universal mineral oil for two-stroke engines. Manufactured using high-quality base oils and a modern additive package.

### Application

**Rosneft MOTO 2T** is designed for use in motorcycles, motorbikes and other equipment with two-stroke gasoline engines, in which, according to the manufacturers' requirements, API TC oils are recommended. The oil is used in a mixture with gasoline in a ratio of 1:50, but one should follow the engine manufacturers' recommendations if a higher dosage is required. The oil is self-miscible and must be added to the tank before refueling.

## APPROVALS AND SPECIFICATIONS

### International specifications:

API TC; JASO FD; ISO I-GD; SAE F/M 2

## BENEFITS

- The oil-fuel mixture burns completely and without residue;
- Highly effective additives in the oil help remove carbon deposits from the combustion chamber;
- Efficiently protects the engine and the entire fuel system from corrosion;
- Fully compatible and interchangeable with oils of the same quality level.

## PACKAGING

1 L, 4 L

## Typical physical and chemical properties

Parameter	Test method	Rosneft MOTO 2T
Kinematic viscosity at 100°C, mm <sup>2</sup> /s	GOST 33	8,67
Viscosity Index	GOST 25371	99
Total Base Number (TBN) , mg KOH/g	GOST 11362	1,1
Sulphated ash, % mass.	GOST 12417	0,08
Flash point, COC °C	GOST 4333	224
Pour Point, °C	GOST 20287	-25
Density at 15°C, kg/m <sup>3</sup>	ASTM D1298	879