



PRODUCT DESCRIPTION AND APPLICATION

Product Description

Rosneft Maximum 10W-30 is a mineral multi-grade engine oil with improved anti-wear properties. Produced from a mixture of high-quality synthetic and mineral components using a modern additive package.

Application

Rosneft Maximum 10W-30 is intended for use in gasoline and diesel engines (including those equipped with a turbocharger) of passenger cars and light-duty commercial vehicles, where API SG/CD or lower service categories are required.

APPROVALS AND SPECIFICATIONS

International specifications:
API SG/CD

BENEFITS

- Protects the engine against wear and corrosion, thus increasing its service life;
- Prevents deposit formation on the engine parts;
- Ensures easy engine start at cold temperatures;
- Compatible with all existing stuffing box seals and protects engine parts from leaks.

PACKAGING

1 L, 4 L, 5 L, 216.5 L

Typical physical and chemical properties

Parameter	Test method	Rosneft Maximum 10W-30
Kinematic viscosity at 100°C, mm ² /s	GOST 33	12,4
Cold Cranking Viscosity (CCS) at - 25°C, mPa·s	ASTM D 5293	6110
Viscosity Index	GOST 25371	147
Total Base Number (TBN) , mg KOH/g	GOST 11362	7,0
Sulphated ash, % mass.	GOST 12417	1,2
Flash point, COC °C	GOST 4333	220
Pour Point, °C	GOST 20287	-33
NOACK evaporation loss, %	GOST 32330	14,2
Density at 15°C, kg/m ³	ASTM D1298	877