



PRODUCT DESCRIPTION AND APPLICATION

Product Description

Rosneft Kinetic MT 75W-85 is a modern semi-synthetic multigrade transmission oil designed for use in mechanical transmissions. A special additive package provides increased resistance to oxidation, high anti-wear and extreme pressure properties, as well as the durability of synchronizers and smooth gear shifts.

Application

Rosneft Kinetic MT 75W-85 is recommended for application in all types of mechanical transmissions of motorcycles, passenger cars and commercial vehicles. The oil can be used in hypoid gears of the driving axles, where, in accordance with the manufacturer's requirements, API GL-4 or lower services categories are required.

APPROVALS AND SPECIFICATIONS

International specifications:

API GL-4

Approvals:

AvtoVAZ

BENEFITS

- A modern additive package provides an improved performance and anti-wear protection of mechanical transmissions and synchronizers under high temperature conditions and high contact loads;
- A high level of frictional properties guarantees a reliable operation of the transmission units.

PACKAGING

1 L, 4 L, 20 L, 216.5 L

Typical physical and chemical properties

Parameter	Test method	Rosneft Kinetic MT 75W-85
Kinematic viscosity at 100°C, mm ² /s	GOST 33	13
Cold Cranking Viscosity (CCS) at - 40°C, mPa·s	ASTM D 5293	100 000
Viscosity Index	GOST 25371	168
Flash point, COC °C	GOST 4333	210
Pour Point, °C	GOST 20287	-42
Corrosion influence on metals, merits	GOST 2917	1B
Density at 20°C, kg/m ³	GOST 3900	875