



## PRODUCT DESCRIPTION AND APPLICATION

### Product Description

**Rosneft Maximum 15W-40** is a mineral multi-grade engine oil with improved anti-wear properties. Produced from a mixture of high-quality synthetic and mineral components using a modern additive package.

### Application

**Rosneft Maximum 15W-40** is intended for use in gasoline and diesel engines (including those equipped with a turbocharger) of passenger cars and light-duty commercial vehicles, where API SG/CD or lower service categories are required.

## APPROVALS AND SPECIFICATIONS

**International specifications:**  
API SG/CD

## BENEFITS

- Protects the engine against wear and corrosion, thus increasing its service life;
- Prevents deposit formation on the engine parts;
- Ensures easy engine start at cold temperatures;
- Compatible with all existing stuffing box seals and protects engine parts from leaks.

## PACKAGING

1 L, 4 L, 5 L, 20 L, 216.5 L

## Typical physical and chemical properties

Parameter	Test method	Rosneft Maximum 15W-40
Kinematic viscosity at 100°C, mm <sup>2</sup> /s	GOST 33	15,3
Cold Cranking Viscosity (CCS) at - 20°C, mPa·s	ASTM D 5293	6279
Viscosity Index	GOST 25371	135
Total Base Number (TBN) , mg KOH/g	GOST 11362	7,0
Sulphated ash, % mass.	GOST 12417	0,8
Flash point, COC °C	GOST 4333	220
Pour Point, °C	GOST 20287	-28
NOACK evaporation loss, %	GOST 32330	10,9
Density at 15°C, kg/m <sup>3</sup>	ASTM D1298	888