



PRODUCT DESCRIPTION AND APPLICATION

Product Description

Rosneft Standard 20W-50 is a mineral multi-grade engine oil, which provides a reliable engine protection. Produced from mineral base components using a high-quality package of functional additives.

Application

Rosneft Standard 20W-50 is designed for use in gasoline and diesel engines of passenger cars and light-duty commercial vehicles, where API SF/CC or lower service categories are required.

APPROVALS AND SPECIFICATIONS

International specifications:
API SF/CC

BENEFITS

- The formulation of Rosneft Standard 20W-50 oil is specially designed for use when operating a car in hot climates;
- Reliably protects engine parts and maintains oil pressure in high-mileage vehicles;
- Effectively removes heat from the most heat-loaded engine parts;
- Compatible with all existing stuffing box seals and protects the engine from leaks.

PACKAGING

1 L, 4 L, 5 L, 20 L, 216.5 L

Typical physical and chemical properties

Parameter	Test method	Rosneft Standard 20W-50
Kinematic viscosity at 100°C, mm ² /s	GOST 33	19,5
Cold Cranking Viscosity (CCS) at - 20°C, mPa·s	ASTM D 5293	9000
Viscosity Index	GOST 25371	105
Total Base Number (TBN) , mg KOH/g	GOST 11362	5,6
Sulphated ash, % mass.	GOST 12417	0,8
Flash point, COC °C	GOST 4333	220
Pour Point, °C	GOST 20287	-20
NOACK evaporation loss, %	GOST 32330	12,1
Density at 15°C, kg/m ³	GOST 3900	888