



DESCRIPTION AND APPLICATION AREA

Product description

Rosneft Magnum Ultratec A3 0W-30 is a multigrade fully synthetic engine oil that prevents the deposit formation, providing reliable protection and long engine life, including in active urban driving.

Application area

Rosneft Magnum Ultratec A3 0W-30 engine oil is intended for modern petrol and diesel engines of passenger cars and light commercial vehicles including turbocharged ones, where it is necessary to use oil meeting the requirements of

SN/CF, ACEA A3/B4 or one of the following OEM specifications.

SPECIFICATIONS

API SN/CF;
 ACEA A3/B4;
 BMW Longlife-01;
 GM LL-A/B-025;

MB 229.5;
 Renault RN0700/ RN0710;
 Volvo VCC 95200356;
 VW 502 00/505 00.

ADVANTAGES

- Specially designed to meet the requirements of leading European and American car manufacturers;
- Suitable for vehicles under warranty service;
- Provides reliable wear protection for engine parts;
- High oxidative stability of the oil prevents formation of deposits and sludge;
- Suitable for use in harsh winter conditions, providing easy starting and reliable protection of the engine at the start.

PACKING

1 L, 4 L, 216.5 L

Typical physicochemical parameters

Parameter	Test method	Rosneft Magnum Ultratec A3 0W-30
Kinematic viscosity at 100 °C, mm ² /s	GOST 33/ ASTM D445	10.2
Dynamic viscosity CCS at - 30 °C, mPa·s	ASTM D5293	5760
Viscosity index	GOST 25371/ ASTM D2270	172
Alkalinity, mg KOH/g	ASTM D2896/ GOST 30050	10.5
Sulfate ash content, % wt.	GOST 12417	1.1
Open flash-point, °C	GOST 4333/ ASTM D92	210
Pour point, °C	GOST 20287	-47
Vaporizability according to NOACK, %	ASTM D5800	9.5
Density at 15 °C, kg/m ³	ASTM D4052	849