



DESCRIPTION AND APPLICATION AREA

Product description

Rosneft Magnum Ultratec 5W-30 is a multigrade, universal, fully synthetic engine oil that provides reliable protection and long engine life.

Application area

Rosneft Magnum Ultratec 5W-30 engine oil is intended for modern petrol and diesel engines of passenger cars and light commercial vehicles including turbocharged ones, where it is necessary to use oil meeting the requirements of API SL/CF, ACEA A5/B5 or Renault RN0700 OEM specification.

SPECIFICATIONS

API SL/CF;
 ACEA A5/B5;
 Renault RN0700

ADVANTAGES

- Specially designed to meet the requirements of international specifications;
- Provides reliable protection and long engine life;
- Has a reduced burning oil consumption.

PACKING

1 L, 4 L, 216.5 L

Typical physicochemical parameters

Parameter	Test method	Rosneft Magnum Ultratec 5W-30
Kinematic viscosity at 100 °C, mm ² /s	GOST 33/ ASTM D445	12.1
Dynamic viscosity CCS at - 30 °C, mPa·s	ASTM D5293	5900
Viscosity index	GOST 25371/ ASTM D2270	160
Alkalinity, mg KOH/g	ASTM D2896/ GOST 30050	10.0
Sulfate ash content, % wt.	GOST 12417	1.0
Open flash-point, °C	GOST 4333/ ASTM D92	210
Pour point, °C	GOST 20287	-40
Vaporizability according to NOACK, %	ASTM D5800	10.0
Density at 15 °C, kg/m ³	ASTM D4052	863