



Petroleum paraffin wax T-2

Petroleum paraffin wax T-2 (Bashneft) is used for use in the chemical, petrochemical industry and in other sectors of the national economy.

TYPICAL PARAMETERS

Specification Test	Test method	Petroleum paraffin wax T-2
Appearance	Observation	the crystalline mass is white with shades of yellow
Melting point, °C	GOST 23683 Application A	56,0
Oil Content, wt %	GOST 9090	1,46
ASTM Color	GOST 25337-82	12
Mechanical impurities, wt %	GOST 6370	absence
The content of water-soluble acids and alkalis	GOST 6307-75	absence
Pour Point, °C	ASTM D 938	56,0
Density at 70 °C, kg/m ³	EN ISO 12185	775,2
Cone penetration of unmixed product at 25 °C, 0.1 mm	ASTM D 217	6
Cone penetration of unmixed product at 25 °C, 0.1 mm	ASTM D 937	5
Colorimetric characteristic, ASTM units	ISO 2049 (equivalent ASTM D1500)	0,5
Kinematic Viscosity at 100 °C, mm ² /s	ASTM D 445 (GOST 33)	3,855
Flash Point, COC, °C	GOST 4333	216
Density at 20 °C, kg/m ³	GOST 3900 (Method 1)	816,1
The aggregate state is at 20 °C and 760 mmHg.	Observation	Solid