



DESCRIPTION AND APPLICATION AREA

Product description

Rosneft Magnum Ultratec 10W-40 is a multigrade, universal, fully synthetic engine oil that provides reliable protection and long engine life.

Application area

Rosneft Magnum Ultratec 10W-40 engine oil is intended for modern petrol and diesel engines of passenger cars and light commercial vehicles including turbocharged ones, where it is necessary to use oil meeting the requirements of API SN/CF, ACEA A3/B4 or one of the following OEM specifications.

SPECIFICATIONS

API SN/CF;
 ACEA A3/B4;
 MB 229.3;
 VW 502.00/505.00;
 GM LL-A/B-025;

Renault RN0700/ RN0710;
 Fiat 9.55535-G2;
 PSA B71 2300;
 AVTOVAZ, JSC

ADVANTAGES

- Specially designed to meet the requirements of international specifications;
- Provides reliable protection and long engine life;
- Has a reduced burning oil consumption.

PACKING

1 L, 4 L, 216.5 L

Typical physicochemical parameters

Parameter	Test method	Rosneft Magnum Ultratec 10W-40
Kinematic viscosity at 100 °C, mm ² /s	GOST 33/ ASTM D445	13.1
Dynamic viscosity CCS at - 30 °C, mPa·s	ASTM D5293	4500
Viscosity index	GOST 25371/ ASTM D2270	160
Alkalinity, mg KOH/g	ASTM D2896/ GOST 30050	10.0
Sulfate ash content, % wt.	GOST 12417	1.25
Open flash-point, °C	GOST 4333/ ASTM D92	220
Pour point, °C	GOST 20287	-47
Vaporizability according to NOACK, %	ASTM D5800	10.0
Density at 15 °C, kg/m ³	ASTM D4052	860