

PRODUCT DESCRIPTION AND APPLICATION



Product Description

Rosneft Revolux GEO Plus 15W-40 is a high quality medium-ash engine oil for spark ignition engines using propane-butane mixture (LPG) as fuel. It is produced from highly refined petroleum base oils and modern additives.

Application

Rosneft Revolux GEO Plus 15W-40 is intended for all-season use in gas engines of buses, line-haul trucks and other commercial vehicles operating on propane-butane mixture (LPG).

APPROVALS AND SPECIFICATIONS

International specifications:

API CF

BENEFITS

- High resistance to oxidation and nitration ensures the oil's long service life;
- Balanced composition of detergent-dispersant additives keep the engine parts clean throughout the oil service interval;
- Rosneft Revolux GEO has an excellent compatibility with all existing seal materials, and thus protects the car engine from leaks.

PACKAGING

216.5 L, 1000 L

Typical physical and chemical properties

Parameter	Test method	Rosneft Revolux GEO Plus 15W-40
Kinematic viscosity at 100 °C, mm ² /s	ASTM D445	15,6
Cold Cranking Viscosity (CCS) at – 20 °C, mPa·s	ASTM D 5293	6250
Viscosity Index	ASTM D2270	135
Total Base Number (TBN) , mg KOH/g	ASTM D4739	6,4
Sulphated ash, % mass.	GOST 12417	0,9
Flash point, COC °C	ASTM D92	217
Pour Point, °C	ASTM D97	-27
Density at 15°C, kg/m ³	ASTM D4052	884